
Wagtail test utilities Documentation

Release 0.1.0

Tim Heap

November 25, 2015

1	Reference	3
1.1	WagtailPageTests	3
2	Indices and tables	5
	Python Module Index	7

Contents:

1.1 WagtailPageTests

class wagtailtestutils.utils.**WagtailPageTests**

assertCanCreateAt (*parent_model, child_model, msg=None*)

Assert a particular child Page type can be created under a parent Page type. *parent_model* and *child_model* should be the Page classes being tested.

Example:

```
# You can create a ContentPage under a HomePage
self.assertCanCreateAt(HomePage, ContentPage)
```

assertCannotCreateAt (*parent_model, child_model, msg=None*)

Assert a particular child Page type can not be created under a parent Page type. *parent_model* and *child_model* should be the Page classes being tested.

Example:

```
# You can not create a ContentPage under an EventPage
self.assertCannotCreateAt(EventPage, ContentPage)
```

assertCanCreate (*parent, child_model, data, msg=None*)

Assert that a child of the given Page type can be created under the parent, using the supplied POST data.

parent should be a Page instance, and *child_model* should be a Page subclass. *data* should be a dict that will be POSTed at the Wagtail admin Page creation method.

Example:

```
# Get the HomePage
root_page = HomePage.objects.get(pk=2)

# Assert that a ContentPage can be made here, with this POST data
self.assertCanCreate(root_page, ContentPage, {
    'title': 'About us',
    'body': 'Lorem ipsum dolor sit amet'
})
```

assertAllowedParentPageTypes (*child_model, parent_models, msg=None*)

Test that the only page types that *child_model* can be created under are *parent_models*.

The list of allowed parent models may differ from those set in *Page.parent_page_types*, if the parent models have set *Page.subpage_types*.

Example:

```
# A ContentPage can only be created under a HomePage
# or another ContentPage
self.assertAllowedParentPageTypes(
    ContentPage, {HomePage, ContentPage})

# An EventPage can only be created under an EventIndex
self.assertAllowedParentPageTypes(
    EventPage, {EventIndex})
```

assertAllowedSubpageTypes (*parent_model*, *child_models*, *msg=None*)

Test that the only page types that can be created under *parent_model* are *child_models*.

The list of allowed child models may differ from those set in `Page.subpage_types`, if the child models have set `Page.parent_page_types`.

Example:

```
# A ContentPage can only have other ContentPage children
self.assertAllowedSubpageTypes(
    ContentPage, {ContentPage})

# A HomePage can have ContentPage and EventIndex children
self.assertAllowedParentPageTypes(
    HomePage, {ContentPage, EventIndex})
```

Indices and tables

- `genindex`
- `modindex`
- `search`

W

wagtailtestutils.utils, 3

A

`assertAllowedParentPageTypes()` (wagtailtestutils.utils.WagtailPageTests method), 3
`assertAllowedSubpageTypes()` (wagtailtestutils.utils.WagtailPageTests method), 4
`assertCanCreate()` (wagtailtestutils.utils.WagtailPageTests method), 3
`assertCanCreateAt()` (wagtailtestutils.utils.WagtailPageTests method), 3
`assertCanNotCreateAt()` (wagtailtestutils.utils.WagtailPageTests method), 3

W

`WagtailPageTests` (class in wagtailtestutils.utils), 3
`wagtailtestutils.utils` (module), 3